

Visit the **Omni-ID Store** at <u>www.omni-id.com</u> to learn more about the complete line of Omni-ID RFID products.

Exo Range – Encased

Product Name Typical Applications		Exo 210 Tool tracking. Attachment to small industrial assets for maintenance applications.	Exo 600 Logistics & Postal Industries. Automotive. Retail & warehousing.	Exo 700 Weapons. Tool & Die. Industrial Assets.	Exo 750 Automotive Supply Chain. Logistics and Postal. Manufacturing tote tracking.	Exo 800 Manufacturing tote tracking. Logistics and Postal. Retail supply chain.	Exo 800P Flexible	Exo 800P Rigid Plastic RTIs and containers Plastic pallets Non-metallic industrial assets
RF Specifications	Frequency Range (MHz)	866–868 (EU) 902–928 (US)	860–940 (GS)	865.6–867.6 (ETSI) 915–925 (FCC)	860–930 (GS)	860–940 (GS)	860–940 (GS)	860–940 (GS)
	Read Range (m) – Fixed reader Handheld reader	Up to 3.0 Up to 1.8	Up to 6.0 Up to 3.0	Up to 5.5 Up to 3.5	Up to 8.0m (US), 7.0m (EU) Up to 4.0m (US), 3.5m (EU)	Up to 8.0	Up to 8.0	Up to 8.0
	Material Compatibility	Optimized for Metal substrates	Optimized for Metal substrates	Optimized for Metal substrates	Optimized for Metal substrates	Optimized for Metal substrates	Optimized for plastic substrate	Optimized for plastic substrate
	ІС Туре	Alien Higgs 3	Impinj Monza 4QT	Alien Higgs 3	Impinj Monza 4QT	Impinj Monza 4QT or Alien Higgs 3	Alien Higgs 3	Alien Higgs 3
Physical and Environmental Specifications	Encasement	Durable Thermoplastic Material	ABS Rigid Plastic	Durable Thermoplastic Material	ABS Rigid Plastic	ABS Rigid Plastic	PVC	ABS Rigid Plastic
	Size (mm)	63 × 9.75 × 3.6	$80 \times 15 \times 12.2$ (with holes) $60 \times 15 \times 12.2$ (without holes)	30 × 21 × 6.35	51.0 × 48.0 × 12.6	110 × 25.0 × 12.85	96 × 28 × 1.3	105 × 36 × 3.5
	Weight (g)	2.1	12.5 (with holes) 11.5 (without holes)	75	25.6	26	2.7	11.6
	Operating Temperature Max Exposure Temp (°C)	-40 to +85 +105	-40 to +85 +105	-20 to +85 +105	-40 to +65 +105	-40 to +85 +105	-20 to +65 +65	-40 to +85 +85
	Ingress Protection	IP68	IP68	IP68	IP68	IP68	IP68	IP68
	Shock and Vibration	MIL STD 810-F	MIL STD 810-F	MIL STD 810-F	MIL STD 810-F	MIL STD 810-F	MIL STD 810-G	MIL STD 810-G
	Attachment	Industrial Foam Tape	Mechanical (std.)	Film adhesive (std.)	Mechanical (std.)	Mechanical (std.)	Rivet/Screw/Adhesive	Rivet/Screw/Adhesive
	Order Codes*	057-US, EU	061-GS	095-GS	078-GS	077-GS	111-GS	104-GS

* Order Option Codes are listed on the datasheets.