

SlimFlex™ Tag

Pliable RFID tags mount anywhere and endure rugged conditions



HID Global® SlimFlex™ RFID tags are among the most advanced general purpose flexible tags available. The unique thermoplastic polyurethane (TPU) housings – made from the same materials used worldwide to manufacture automobile pipes and hoses – tolerate repeated bending or torsion, while maintaining excellent performance characteristics. The durable housing safeguards embedded electronics, even under harsh conditions.

SlimFlex passive contactless transponders improve data collection speed and accuracy for logistics applications.

Anti-collision functionality, fast data-rate communication and password data protection enable precise, reliable reading and updating of each tag's large user memory. SlimFlex tags are compliant with ISO certified readers and modules. All SlimFlex RFID tags are waterproof. They can be used in deep-sea operations, provide high resistance to aggressive liquids

and UV rays, and deliver reliable performance and reading stability at high and sub-freezing temperatures.

Available in multiple configurations:

- Rectangular **SlimFlex tags** attach snugly to round or irregular surfaces, such as cylindrical containers, plastic pipes, helmets or even trees. These tags conform to surface contours, and can be securely attached with cable ties, industrial adhesives, rivets or screws.
- The **SlimFlex Tag Washer** has been designed with one reinforced hole to rivet it. This version is ideal whenever a SlimFlex tag shall be fixed with a single rivet to hang down from metal bars or be placed on a hook.



KEY BENEFITS:

- **Flexibility** – Repeated bending will not impede performance; enables secure mounting on rounded or irregular surfaces
- **High durability** – Resistant to liquids, dust, impact and weather extremes
- **Enhanced reliability** – Precise, consistent read ranges when mounted to plastic or wood

TECHNOLOGY HIGHLIGHTS:

- HF 13.56 MHz version readable with ISO/IEC 15693 compatible NFC devices with tag option for on-metal use.
- Broadband UHF version for worldwide use at 860 to 960 MHz.
- Fully interoperable, standards compliant.
- Bendable, durable housing.
- Waterproof; resistant to chemicals, impact and UV rays.
- Large user memory.
- 1D barcode laser engraved optional

APPLICATION AREAS:

Asset tracking and logistics

- Inventory management
- Itemize tracking of pallets and goods
- Cylindrical items such as plastic bins or tree trunks

Laundry, medical & health

- Uniform companies
- Commercial laundry
- Hospital laundry
- Medical compartments

Returnable transport items

- Shipping container or pallet tracking
- Waste management
- Commercial and industrial plastic bin identification

	SlimFlex™ Tag						
	HF		Standard	UHF			Washer
	200	OM (on-metal)		200	301	Mini	
							
Base Model Number	629990 (blank) 629990-020 (1D barcode)	62999C-101 (Yellow) 62999C-102 (White)	6M6990-101	6M6990-200 6M6990-220 (1D barcode)	6M6990-300	6H2992-200	6M6990-400
ELECTRONIC							
Operating Frequency	13.56 MHz		865-928 MHz (Global)				
Chip Type	ICODE SLiX		M730			MR6-P	M730
Memory	1024 bit EEPROM		128 bit EPC			128/96 bit EPC, 32/64 bit UM	
Anti-Collision	Yes						
Reading Distance (2W reader ERP, free space)	Up to 19.7 ft (6 m)			Up to 13.1 ft (4 m)		Up to 19.7 ft (6 m)	
PHYSICAL							
Dimensions	3.3 x 1.0 x 0.1 in (83 x 25 x 3 mm)	3.3 x 1.0 x 0.2 in (83 x 25 x 6 mm)	3.0 x 1.0 x 0.1 in (77 x 25 x 3 mm)	3.3 x 1.0 x 0.12 in (83 x 25 x 3 mm)	3.4 x 1.0 x 0.1 in (87 x 25 x 3 mm)	2.5 x 0.5 x 0.08 in (65 x 12 x 2 mm)	4.3 x 1.0 x 0.1 in (110 x 25 x 3 mm)
Mounting Method	Cable tie, glue, rivet, screw	Cable tie	Glue, rivet, screw	Cable tie vertical to surface, glue, rivet, screw	Cable tie flush with surface, glue, rivet, screw	Cable tie, glue, rivet, screw	Aluminum Rivet
Fixation Hole Size	0.2 x 0.1 in (6 x 2.5 mm)		Ø 0.1 in (3 mm)	0.2 x 0.1 in (6 x 2.5 mm)	Ø 0.27 in (7 mm)	0.25 x 0.08 in (6.5 x 2 mm)	Ø 0.18 in (4.8 mm)
Affixes To	Any material (vertical mount)	Any material (flat mount)	Plastic, dry wood	Any material (vertical mount)	Plastic, dry wood	Any material (vertical mount)	
Housing Material	TPU					TPU	
Color	Yellow (Pantone 108)	Yellow (Pantone 108) White (RAL 9016)	Green	Yellow (Pantone 108)		White	Yellow
Weight	0.2 oz (6 g)	0.3 oz (8.5 g)	0.2 oz (6 g)		0.05 oz (1.4 g)		0.3 oz (9 g)
CHEMICAL AND MECHANICAL RESISTANCE							
Water	IP68, 68° F (20° C), 6.6 ft (2 m) x 24 h						
Withstands Exposure To	Mineral oil, petroleum, salt mist, vegetable oil, HCL (10%), Bleach (5%), UV light						
Environmental Test Conditions	68° F (20° C), 100 h						
Vibration	IEC 68.2.6 [10 g, 10 to 2000 Hz, 3 axis, 2.5 h]						
Shock	IEC 60068-2-27:2008 [40 g, 18 ms, 6 axis, 2000 times]						
Axial / Radial Force	1000 N, 10 sec						
Water Press Extraction (set point)						70 bars (5 min)	
Impact	IEC 62262-IK06						
Drop Test	100 drops 5.9 ft (1.8 m)						
Bending	5.9 in (150 mm) curve radius					5.9 in (150 mm) curve radius	
THERMAL							
Storage	-40° to +158° F (-40° to +70° C)						
Operating Temperature	-40° to +158° F (-40° to +70° C)						
Peak	212° F (100° C), 100 h						
Shock/Fatigue	-40° to +158° F (-40° to +70° C), 100 x 5 min with 30 sec transition						
OTHER							
Standards	ISO/IEC 15693, 18000-3 Mode 1, NFC Tag Type 5 (if NDEF formatted)		UHF EPC Class 1 Gen 2, ISO 18000-6C, RAIN				
Options	Laser engraving, custom encoding, alternate colors		Custom embossed logo, alternate colors	Laser engraving, custom embossed logo, alternate colors			
Box Size	1,000 pcs.	500 pcs.	500 pcs.	1,000 pcs.		1,000 pcs.	
Warranty	2 Years						



hidglobal.com

North America: +1 512 776 9000 | Toll Free: 1 800 237 7769
 Europe, Middle East, Africa: +353 91 506 900
 Asia Pacific: +852 3160 9800 | Latin America: +52 55 9171 1108
For more global phone numbers click here

For more information, contact tagsales@hidglobal.com