


## NFC Etikett NTAG213 - 8,5x17mm - Transparent PET

---



NFC etikett i litet format som kan läsas även med en smart telefon. Etiketten är lämplig för märkning av inventarier och perfekt för ID. Taggen fungerar INTE på metall. Password-protectable.

Produktnummer: ITN-AD754

### NTAG213 Stickers Technical Specifications

- Integrated Circuit (IC): NXP NTAG213
- Air interface protocol: ISO 14443 A
- Operation Frequency: 13.56 MHz
- Memory: 144 bytes
- Operating temperature: from -25°C to 70°C / from -13°F to 158°F
- ESD voltage immunity: ±2 kV peak HBM
- Bending diameter: > 50 mm, tension less than 10 N
- Model: AD-754D NTAG213

### Dimensioner

- Antenna size: 16 x 7.5 mm
- Die-cut size: 17 x 8.5 mm

### Material

- Transponder face material: Clear PET
- Transponder antenna material: Etched Aluminum

## Tekniska data

### Data sheet

NFC Chip	NXP NTAG213
NFC Standard	ISO/IEC 14443-A
Universal Compatibility	Yes
UID (Unique ID)	7 bytes
Available Memory	144 bytes
Communication Rate	106 kbit/s
Encryption	Not supported
Read/Write Endurance	100,000 cycles
Data Retention	10 years
Works On Metal	No
Password Protection	Supported
Commodity Code (HS)	85235200

The NTAG213 chip is compatible with all Android 4.4+ smartphones and all iPhones 7 and later.