



C66

Mobile Computer



Android



4G



WiFi



Bluetooth



1D Barcode



2D Barcode



NFC



UHF



Camera



GPS

Chainway C66 is a newly-developed rugged handheld computer with large screen and strong extensibility. Based on Android 9.0 OS, it is equipped with Qualcomm octa-core processor for high-speed processing. With 5.5-inch high-definition display, it is integrated with barcode scanning, NFC and other functions. The data collection device supports quick charge and UHF sled for good extensibility that can meet the needs in logistics, warehouse, manufacturing, retail, asset tracking, power patrol inspection, etc.



UHF



UHF Sled Reader



Pistol Grip

Specification

Physical Characteristics

Dimensions	160.0 x 76.0 x 15.5 mm / 6.3 x 2.99 x 0.61 in.
Weight	287 g / 10.12 oz. (device with battery)
Keypad	1 power key, 2 scan keys, 2 volume keys, 1 PTT key
Battery	4300 mAh removable main battery, 5200 mAh optional pistol battery, support QC3.0 and RTC Standby: over 300 hours (only main battery) Continuous use: over 12 hours (depending on user environment) Charging time: 2.5 hours (charge device by standard adaptor and USB cable)
Speaker	Support
Vibrator	Support
Microphone	2 Microphones, 1 for noise reduction
Display	5.5-inch high definition full display (18:9), IPS LTPS 1440*720
Touch Panel	Corning Gorilla Glass, multi-touch panel, gloves and wet hands supported
Sensor	Gravity sensor, proximity sensor, light sensor, accelerometer sensor, vibration motor
Indicator LED	Power, charging, status indicator
Card slot	2 slots for SIM card, 1 slot for TF card
Interfaces	USB3.0, Type-C, OTG, extended thimble

Performance

CPU	Qualcomm 1.8 GHz Octa-core
RAM+ROM	2GB+16GB / 3GB+32GB
Expansion	Supports up to 128 GB Micro SD card

Developing Environment

Operating System	Android 9.0: GMS, Android Enterprise, Zero-Touch, FOTA, Soti MobiControl, SafeUEM supported
SDK	Chainway Software Development Kit
Language	Java
Tool	Eclipse / Android Studio

User Environment

Operating Temp.	-20 °C~+50 °C
Storage Temp.	-40 °C~+70 °C
Humidity	5% RH - 95% RH non condensing
Drop Specification	Multiple 1.5 m / 4.92 ft. drops (at least 20 times) to the concrete across the operating temperature range Multiple 2.4 m / 7.87 ft. drops (at least 20 times) to the concrete after installed rubber bumper
Tumble Specification	1000 x 0.5 m/1.64 ft falls at room temperature
Sealing	IP65 per IEC sealing specifications
ESD	±15 KV air discharge, ±8 KV conductive discharge

Communication

WLAN	Support 802.11 a/b/g/n/ac
WWAN (Europe, Asia)	2G: 850/900/1800/1900 MHz 3G: CDMA EVDO: BC0 WCDMA: 850/900/1900/2100MHz TD-SCDMA: A/F(B34/B39) 4G: B1/B3/B5/B7/B8/B20/B38/B39/B40/B41

WWAN(America)	2G: 850/900/1800/1900MHz 3G: 850/900/1900/2100MHz 4G: B2/B4/B5/B7/B12/B17/B38
Bluetooth	Bluetooth 4.2/4.1+HS/4.0/3.0+HS/2.1+EDR
GNSS	GPS/AGPS, GLONASS, BeiDou, internal antenna

Data Collection

Camera

Rear Camera	Rear 13MP Autofocus with flash
--------------------	--------------------------------

NFC

Frequency	13.56 MHz
Protocol	ISO14443A/B, ISO15693, NFC-IP1, NFC-IP2, etc.
Chips	M1 card (S50, S70), CPU card, NFC tags, etc.
Range	2-4 cm

UHF1 (Optional)

Engine	CM2000-1 module based on Impinj Indy R2000
Frequency	865-868 MHz / 920-925 MHz / 902-928 MHz
Protocol	EPC C1 GEN2 / ISO18000-6C
Antenna	Circular Polarized Antenna (4 dBi)
Power	1W (30 dBm, +5 dBm to +30 dBm adjustable) 2W Optional (33 dBm, for Lati America, etc.)
R/W range	>25 m (indoors); >15 m (open outdoors, Impinj MR6 tag)
Reading rate	>200 tags/s
Communication Mode	Pin Connector

UHF2 (Optional, UHF Sled)

Engine	CM2000-1 module based on Impinj Indy R2000
Frequency	865-868 MHz / 920-925 MHz / 902-928 MHz
Protocol	EPC C1 GEN2 / ISO18000-6C
Antenna	Circular Polarized Antenna (3 dBi)
Power	1W (30 dBm, support +5~+30 dBm adjustable) 2W Optional (33 dBm, for Lati America, etc.)
R/W range	>22 m (indoors); >10 m (open outdoors, Impinj MR6 tag)
Reading rate	>200 tags/s
Communication Mode	Pin Connector / Bluetooth

*Ranges and rates depend on tags and environment

Barcode Scanning (optional)

2D Scanner	Zebra: SE4710/SE2100; Honeywell: N6603
1D Symbologies	UPC/EAN, Code128, Code39, Code93, Code11, Interleaved 2 of 5, Discrete 2 of 5, Chinese 2 of 5, Codabar, MSI, RSS, etc.
2D Symbologies	PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, MaxiCode; Postal Codes: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal, Dutch Postal (KIX), etc.

Optional accessories(See details in Accessory Guide)

Separate handle with one button;
Handle + battery (handle battery 5200 mAh, one button) ;
UHF back clip + handle (5200 mAh, one button) ;
Wrist Strap; Rubber Bumper; Charging Cradle

Notice: Product specifications are subject to change without prior notice. / Model: C66 / Update Date: 2019-11-06

CHAINWAY®

Shenzhen Chainway Information Technology Co., Ltd

Address: 9F, Building2, Phase 2, Gaoxinqi Industrial Park, Liuxian 1st Rd., Bao'an District, Shenzhen, Guangdong 518102, China

Tel: 0086-755-23223316

Fax: 0086-755-23223310

Email: sales@chainway.cn

Web: http://www.chainway.net